

Table of Contents

iii	Australian Centre for Geomechanics
v	Committees
vii	Technical Reviewers
ix	Preface
xi	Sponsors

Keynote

3	Developments in treating and dewatering oil sand tailings <i>J.C. Sobkowicz, Thurber Engineering Ltd., Canada</i>
---	--

Thickened and Paste Tailings

21	Paste deposition over an existing subaqueous slurry deposit of high sulphide content tailings – the Neves Corvo experience <i>R. Lopes, Golder Associates Brasil Consultoria e Projetos Ltda., Brazil; R. Bahia, Golder Associates Portugal Unipessoal Lda., Portugal; M. Jefferies, Golder Associates Ltd., Canada; M. Oliveira, Somincor, Portugal</i>
37	Paste and thickened tailings – myth busting and clarification <i>T.G. Fitton and K.D. Seddon, ATC Williams Pty Ltd, Australia</i>
47	Dry stacking of cyclone tailings <i>W.G. Lugão, M.M. Almeida, A.O. Guimarães and F.S. Magalhães, VOGBR, Brazil; S.D.S. Mohallem, ArcelorMittal, Brazil</i>
61	The effect of process variations on slurry rheology, washer performance and control strategy <i>F. Sofra and A.P. Knight, Rheological Consulting Services Pty Ltd, Australia</i>
75	Desiccation in dewatering and strength development of high-density hard rock tailings <i>P. Simms, S. Sivathayalan and F. Daliri, Department of Civil and Environmental Engineering, Carleton University, Canada</i>
87	Thickening of iron ore tailings slimes using sub-aerial deposition: field experimental observations <i>W.L. Oliveira-Filho, Mining Engineering Department, Federal University of Ouro Preto, Brazil; D.R. Silva and F.E. Almeida, Samarco Mineração S.A., Brazil</i>
101	An evaluation of cyclone performance to improve the quality of cyclone underflow material for tailings disposal <i>J.A. Wates and M.A. Knight, Fraser Alexander, South Africa</i>

Polymer Addition

117	Effects of polymer dosage on dewaterability, rheology, and spreadability of polymer-amended mature fine tailings <i>S. Mizani, S. Soleimani and P. Simms, Department of Civil and Environmental Engineering, Carleton University, Canada</i>
133	Next generation polymeric flocculants for thickening and dewatering <i>H. Kolla, A. Mahmoudkhani, P. Watson and M. Awad, Kemira, USA; P. O'Neill, Kemira, Canada; L.R. Moore, Kemira, USA</i>
147	Development of success criteria for high density fluid fine tailings flocculation in the oil sand industry <i>X.S. Yuan, B. Bara and R. Siman, Research and Development Centre, Syncrude Canada Ltd, Canada</i>
161	BASF novel flocculant technology – benefits for counter current decantation circuits based on pilot-scale trials <i>A. Berger and J. Muhor, Global Development Mining Solutions, BASF SE, Germany; S. Adkins, Global Development Mining Solutions, BASF Performance Products plc., UK</i>
175	The utilisation of a coiled plug flow reactor for the flocculation of kaolin slurry <i>T. Nugraha and A.B. Fourie, School of Civil and Resource Engineering, The University of Western Australia, Australia; Y.K. Leong and L. Avadiar, School of Mechanical and Chemical Engineering, The University of Western Australia, Australia</i>

- 185 Flocculant evaluations in a counter current decanter thickening process: laboratory and field results
L.R. Moore, Kemira, USA; T. Putra, Kemira, Indonesia; A. Mahmoudkhani, Kemira, USA

Filtered Tailings

- 201 Considerations for tailings facility design and operation using filtered tailings
B. Ulrich and J. Coffin, Knight Piésold and Co., USA
- 211 Performance analysis for filtered iron ore tailings disposal
A.M.C. Portes, VOGBR Recursos Hídricos e Geotecnia S.A., Brazil; T. Espósito, Universidade Federal Minas Gerais, Brazil
- 225 Red mud pressure filtration for the alumina refinery's bauxite residue tailings disposal
Q. Avery and K. Wilson, FLSmidth, USA
- 239 Evaluation of field compaction of a filtered residue from alumina production
K.D. Nery and L.F.S. Villar, UFMG, Brazil; R.A. Moreno, CBA – Companhia Brasileira de Alumínio, Brazil; J.P. Freire Neto and M. Scarminio, Pimenta de Ávila Consultoria, Brazil; R.S. Junior, CBA – Companhia Brasileira de Alumínio, Brazil
- 249 Geotechnical-geochemical and operational considerations for the application of dry stacking tailings deposits – state-of-the-art
J.L. Lara, E.U. Pornillos and H.E. Muñoz, Golder Associates Peru S.A., Peru
- 261 Geotechnical parameters of iron ore tailings from the Quadrilátero Ferrífero after different treatments and ore processing
J.P.S. Silva, University of São Paulo (USP), Brazil; M.B. Mendes, J.G. Milonas, W. Pirete and W.J. Souza, Vale S.A., Brazil

Comparative Studies

- 275 Filtered tailings versus thickened slurry: four case studies
T.G. Fitton and A. Roshdieh, ATC Williams Pty Ltd, Australia
- 289 Comparative evaluation of surface disposal of thickened versus slurry tailings
D. Johnson, R. Moghaddam and I. Bin Ahmed, Golder Associates Ltd., Canada; C. Laroche, Osisko Mining Corporation, Canada
- 303 Surface erosion effect on tailings
M. Mussé, Environment and Infrastructure, AMEC International Ingeniería y Construcción Ltda., Chile; J. Lupo, Newmont Mining Company, USA
- 313 The Alberta Oil Sands Tailings Roadmap Project
J.C. Sobkowicz, J.E.S. Boswell, M.D. Kofoed and I.D.C. Gidley, Thurber Engineering Ltd, Canada
- 327 New projects – conventional or high density tailings?
D. Romo and R. Martinson, Paterson & Cooke South America Ltda., Chile
- 341 Multi-criteria decision-making tool to support the selection of a tailings disposal system
F.F.G. Santos, Capital Projects Management, Brazil; G.E.S. Valadão and P.R.M. Viana, Mining Engineering Department, Universidade Federal de Minas Gerais, Brazil
- 349 Study of environmental feasibility of paste and thickened tailings by life-cycle assessment
A. Fernandez-Iglesias, ArcelorMittal, Spain; A. Corrêa de Araujo, ArcelorMittal, France; S. Andrés, ArcelorMittal, Spain; W. Xuan, ArcelorMittal, France; R. Luiña and V. Álvarez, Project Engineering Department, University of Oviedo, Spain
- 365 Coarse laden in situ nonwoven geofabrics
D.C. Rennard and J. Medrano, Unconventional Resources, ExxonMobil, USA; A. Ortiz Gomez and T.R. Palmer, Imperial Oil Canada; P.L. Tanaka and S.R. Clingman, Unconventional Resources, ExxonMobil, USA

Mine Backfill

- 379 Full scale experiments on the effectiveness of a drainage system for cemented paste backfill
A. Hasan, G. Suazo and A.B. Fourie, School of Civil and Resource Engineering, The University of Western Australia, Australia

- 393 Next generation dewatering for tailings and paste backfill: E-Disc filter with eductor feed system
K. Nowicki and A. Hellstrand, FLSmidth, USA
- 407 Application of cyclone technology in paste backfill plant design
J. Landriault and P.A. Primeau, Paste Engineering and Design, Golder Associates Ltd., Canada
- 419 Dewatering of tailings for mine backfill with the Boozer disc filter
M. Hatzenbühler, BOKELA do Brasil; J. Hahn and R. Bott, BOKELA GmbH, Germany
- 431 Cemented paste production provides opportunity for underground ore recovery while solving tailings disposal needs
N.C. Gridley, Anglo American Chile, Chile; L. Salcedo NYRSTAR, Chile
- 443 Paste fill – a safety solution for pillar mining
P.R.B. Cavalcante, Mineração Caraiba S.A., Brazil; F. Palkovits, KOVIT Engineering Ltd., Canada

Beach Slopes

- 457 Flow through tilt flume testing for beach slope evaluation at Chuquicamata Mine Codelco, Chile
B. Pirouz and K.D. Seddon, ATC Williams Pty Ltd, Australia; C. Pavvich, ATC Williams Pty Ltd, Australia (previously Codelco-VP); P. Williams, Paul Williams Pty Ltd, Australia; J. Echevarria, Codelco-VP, Chile
- 473 Analysis and flow behaviour prediction of paste material in sheet flow
P.T. Slatter, ATC Williams Pty Ltd, Australia
- 481 Comparison of predictions of beach slopes using alternative models
J. Covacevich, Hatch Associates, Chile; J.A. Wates, Fraser Alexander, South Africa; S. Dal Pozzo, Codelco Andina, Chile
- 493 A tailings beach slope model featuring plug flow
T.G. Fitton and P.T. Slatter, ATC Williams Pty Ltd, Australia

Transport

- 507 Pipe loop tests at Codelco pilot plant
L. Martinson and R. Martinson, Paterson & Cooke, Chile; R. Cooke, Paterson & Cooke, USA
- 521 Pulsation free hydraulically driven piston pump
C. Karambalis, GEHO pumps, Weir Minerals Netherlands, The Netherlands
- 531 Pumping a 100–600 Pa yield stress clay slurry with a centrifugal pump
J.M. Furlan and R.J. Visintainer, Department of Engineering and R&D, GIW Industries, USA; A. Sellgren, Luleå University of Technology, Sweden

Poster Papers

- 547 A model for technology development in oil sands tailings
I.D.C. Gidley and J.E.S. Boswell, Thurber Engineering Ltd., Canada
- 559 Pipeline wear solution at Kidd Mine: energy absorbent ceramic composites
A. White, Xstrata Copper, Canada; M. McGuinness, Paterson & Cooke, Canada; V. Newman, Xstrata Copper, Canada
- 567 Dual inorganic–organic flocculating systems for treatment of oil sands tailings
A. Mahmoudkhani, R. Tellakula, K. Stewart, P. Watson and H. Kolla, Kemira, USA
- 581 Design of a multi-purpose plant to provide paste fill, hydraulic fill, concrete and shotcrete
M. Wallgren, ISL Machinery Inc., Canada; F. Palkovits, KOVIT Engineering Ltd., Canada
- 591 Design of open channels for non-Newtonian fluids
D.A. Rojas, Bechtel, Chile; R.H.A. Janssen, Bechtel, Australia
- 605 Trends in mine tailings disposal from a global perspective and in Brazil
M. e Silva Marques and F.A. Pérez, Golder Associates Peru S.A., Peru

- 615 Key aspects to consider in the design of facilities that comprise a tailings deposit at high concentrations
M. Barrientos and A. López, AMEC International (Chile) S.A., Chile
- 623 Water recovery – a challenge for modern dewatering technology
G. Görres and J. Palmer, Outotec (Filters) Oy, Finland
- 635 Studying feasibility of paste and thickened tailings at laboratory scale – pilot thickeners
A. Fernandez-Iglesias, ArcelorMittal, Spain; A. Corrêa de Araujo, ArcelorMittal, France; M. Goosens, Independent Consultant, Brazil
- 651 Constitutive relation between void ratio undrained shear strength for iron fine tailings
D.C.R. Penna, Pimenta de Ávila Consultoria, Brazil; W.L. Oliveira-Filho, Universidade Federal de Ouro Preto, Brazil
- 661 Author Index